



FIG 048 - ADAPTOR MALE (SOLVENT WELD)



ITEM CODE	METRIC mm	D	D1	d	d1	L	L1	H	R
048/0020x0015	20 x ½"	28.6		20	12	16.5		38.5	½"
048/0020x0020	20 x ¾"								
*048/0025x0020x0015	25 x 20 x ½"	25	32	20		17	19.5	46	½"
048/0025x0020	25 x ¾"	34		25	17	19.5		44	¾"
048/0025x0025	25 x 1"								
048/0032x0025	32 x 1"	42.3		32	22	25.5		52.5	1"
048/0032x0032	32 x 1¼"								
*048/0040x0032x0025	40 x 32 x 1"	40	43	32		32.5	26.5	57	1"
048/0040x0032	40 x 1¼"	51.4		40	30	26.5		58	1¼"
048/0040x0040	40 x 1½"								
048/0050x0040	50 x 1½"	62.5		50	34.5	31.5		64	1½"
048/0050x0050	50 x 2"								
*048/0063x0050x0040	63 x 50 x 1½"	63	68	50		45	38	72	1½"
*048/0063x0050x0050	63 x 50 x 2"	63	68	50		45	38	78	2"
048/0063x0050	63 x 2"	77.4		63	44.4	38.5		74	2"
048/0075x0050	75 x 2"								
*048/0075x0063x0050	75 x 63 x 2"	75	81	63		51.5	44	85	2"
048/0075x0065	75 x 2½"	91.3		75	57.7	44.5		83.5	2½"
048/0090x0065	90 x 2½"								
*048/0090x0075x0050	90 x 75 x 2"	90	97	75		57	51.5	93.5	2"
048/0090x0080	90 x 3"	109.8		90	66.7	51.5		98.5	3"
*048/0110x0090x0080	110 x 90 x 3"	110	119	90		69.5	61.5	112.5	3"
048/0110x0100	110 x 4"	133		110	88.7	61.5		116.5	4"

TECHNICAL DATA:

Maximum Working Pressure:	Up to 16 BAR (232 PSI)
Temperature range:	0°C - +50°C
Material:	uPVC

SUN RESISTANT UV stabilised
EXTRA STRENGTH Robust construction
PROVEN DURABILITY Manufactured to DIN8063 standards